



Chisel Plow

(3 Tines)

Specifications:-

- Heavy Steel Box V-Type Frame Without Any Nut And Bolt.
- They Are Easily Replaceable Tines That Penetrate Up To 20" Without Much Effort.
- Shovels Are Easily Replaceable.
- Working Width 1.20 Meters.
- Tractor Compatibility 50 – 85 HP.

General	
Type	Mounted Box Frame Type
No. Of Tines	03
Tractor Power Requirement	50 HP or Above
Tine Spacing (Adjustable)	380 mm And 675 mm

Overall Dimensions	
Length	750 mm
Width	1400 mm
Height	1300 mm
Material Specifications	
Main V-Frame	1400 × 110 × 6 mm, Made From M.S. Formed Sheet, Box Type
Mast A-Frame	12 mm M.S. Plate, 100 mm Wide, Integral With Supports
Hitch Bracket	18 – 20 mm Thick M.S. Plate Made To Ride On or Penetrate In The Frame Then Welded
Tine	820 × 180 × 30 mm M.S. Plate With Three Depth Adjustment Grooves 50 – 75 mm Apart
Cutting Wedge On Tine	400 × 30 × 50 mm Hardened Steel
Shovel (Replaceable)	265 × 60 × 30 mm Hardened Steel
Tine Pins	100 × 25 mm M.S. Round
Tine Boxes	05 Nos. Made From 6 mm Thick M.S. Sheet At Least 165 mm Deep With Pin-Hole And Reinforcement Wedges At Top And Bottom To Accommodate Tines With Max. Clearance Of 1 – 2 mm

Parking Stand	01 No. M.S. Box or G.I. Pipe Of 40 mm
Miscellaneous	
Paint	Double Coating After Primer And Surface Finish
Nuts And Bolts	To Be Tightened With Spring Washers
Modifications	To Be Carried Out Free Of Cost, If Required
Warranty	Free: 1 Year For Parts And Service Extended: 5 Years For Parts Supply On Payment