



**Disc Plow**  
**(3 Discs)**

**Specifications:-**

General	
Application	For Deep Tillage Of Hard Soil
No. Of Discs	03
Tilt Angle (Adjustable)	150, 180 & 320
Tractor Power	≥ 60 HP
Overall Dimensions	
Overall Length	2100 mm ± 20 mm
Overall Height	1080 mm ± 10 mm

Overall Width	1150 mm $\pm$ 10 mm
Weight (Approx.)	325 Kg $\pm$ 5 Kg
<b>Material Specifications</b>	
Main Frame	Tubular, Seamless Steel Pipe, 170 mm OD & 6 mm Wall Thickness 6 mm M.S. Sheet
Mast (A-Frame)	6 mm M.S. Sheet
Disc Blade	660 mm Dia. 6 mm Thick, Hardened (HRC $\geq$ 40)
Disc Scraper	6 mm M.S. Sheet
Standard	Tubular, 9 mm Thick M.S. Sheet
Hub & Mounting	Steel Cast With 30 mm Dia. Spindle
Furrow Wheel	508 mm Dia., 6 mm Thick Disc, Hardened Steel (HRC $\geq$ 40)
Parking Stand	Box or U-Shape, 6 mm Thick M.S. Sheet With Spring-Loaded Lock
Bearings	02 Nos. 3780 And 32212 or 02 Nos. 3984 – 20 And 32210 For Each Hub 02 Nos. 3206 And 3207 or 02 Nos. 7206 And 7207 For Furrow Wheel With Seals & Grease System

Miscellaneous	
Paint	Double Coat With Primer After Surface Finish
Nuts And Bolts	To Be Tightened With Spring Washers
Bearings	European Standard or Equivalent
Warranty	Free: 1 Year For Parts And Service Extended: 5 Years For Parts Supply On Payment

Mi