



Hydraulic Tipping Trailer

Specifications:-

Description	Spec. B	Spec. C
Type	Hyd. Tipping	Hyd. Tipping
Capacity	5-Ton	8-10 Ton
Vessel Size	11' * 6.5' * 2'	12' * 7' * 2.5'
Floor	MS Sheet SWG 10	
Side Wall	MS Sheet SWG 12	
Chassis Frame		
Lower Channel	8' * 3'	10' * 3'
Upper Channel	6' * 3'	6' * 3'

Axle Size		
Length	52"	56"
Outer Dia.	5.5"	6"
Wall Thickness	3/8"	3/8"
Rims		
Qty.	02	04
Size	9.00 - 20	9.00 – 20
Tipping Device	Double Acting Heavy Duty Locally Made Ram With Mechanical Linkage	
Tipping Angle	55 Degrees	
Maximum Lift Time	10 Seconds At 1500 – 1789 RPM Of Tractor Engine To Its Full Height In Empty Condition	
Hydraulic Kit For Trolley		
Spool Value	Imported From USA, Italy or U.K Minimum Rod Dia., 20 mm	

Selector Value	Imported From USA, Italy or U.K Minimum Rod Dia., 20 mm	
Hyd. Hoses	Imported From The Above Countries, The Crimping And Hoses Should Bear A Pressure Of 4000 PSI. There Should Be No Joint Between Two Connections	
Quick Attachment Coupler Set	Imported	