

Massey Ferguson MF-260 Tractor (2-WD | 60-HP)

Specifications:-

Performance		
Engine Power At 2,250 RPM	60 (B.S.) HP*	
Torque At 1,400 Engine RPM	212 Nm	
PTO Power At Rated Engine Speed	48 HP**	
* Certified To BS AU 141a: (1971)		
** Manufacturer's Estimate		
Engine		
Туре	Diesel / T 3.1524	

No. Of Cylinders	3	
Injection	Direct	
Bore	91.5 mm	
Stroke	127 mm	
Capacity (Liters)	2.5	
Compression Ratio	15.5.1	
Aspiration	Turbo	
Starting Aid	Thermostat	
Throttle Control	Hand And Foot	
Cooling	Water	
Air Cleaner Type	Oil Bath	
Air Pre-Cleaner	Over Bonnet	
Fuel Filter	Dual	
Fuel Filter Capacity	High Capacity	
Exhaust	Vertical	
Oil Cooler	Air Cooled, Fin Type	
Electrics		
Voltage	12V, Negative Earth	

Battery	118 Ah	
Starter Motor	2.2 KW	
Alternator	32 Amp.	
Clutch		
Туре	Dual Clutch	
Diameter	305*254 mm	
Transmission		
Туре	Sliding Spur	
Number of Gears	8 Forward, 2 Reverse	
Road Speed At 2,250 Engine RPM With	12.4/11-28 Rear Tires	
Gear	Speed (Km/Hr.)	
Forward 1 (First Low)	2.6	
Forward 2	3.8	
Forward 3	5.2	
Forward 4	7.0	
Forward 5 (First High)	10.4	
Forward 6	15.2	
Forward 7	20.8	

Forward 8	27.9	
Reverse 1 (Low)	3.5	
Reverse 2 (High)	14.1	
Power Take-Off		
Туре	Live	
Engine Speed At 540 PTO RPM	1,789 RPM	
Shaft Diameter	35 mm	
No. Of Splines	6	
Hydraulics		
Functions	Draft Control, Position Control, Response Control, Constant Pumping	
Pump Type	Reciprocating Ferguson Pump	
Oil Flow	16 L / min	
Pressure	21 MPa At Normal Operating Temperature	
Lift Capacity With Lower Links Horizontal	2,145 kg	
Lower Links	With Cat. I & II Interchangeable Balls	
Front Axle		
Туре	Box Section, Adjustable	

Steering		
Туре	Manual	
Rear Axle And Brakes		
Brake Type	Oil Immersed, Multi-Disc	
Axle Type	Straddle With Epicyclic Reduction Unit	
Brakes Actuation	Mechanical	
Parking Brake	Hand Lever Operated	
Instrumentation		
Gauges	Tachometer, Houmeter, Fuel Level, Battery Condition & Water Temperature Direction Indicators	
Warning Lights	Direction Indicators, Electric Charge, Headlight Main Beam, Low Engine Oil Pressure, Brake Lights & Auxiliary Socket	
Tires		
Front	7.50-16 (6 PR)	
Rear	14.9/13-28 (6 PR)	
Track Adjustment		
Front	1,245 – 1,854 mm	

Rear	1,423 – 2,134 mm	
Weight And Dimensions (Approx.)		
(With 6.00-16 Front And 12.4/11-28 Rear Wheel And With Full Fuel, Oil, And Water)		
Weight		
Gross Weight (Approx.)	1,900 kg	
Dimensions		
Wheel Base	1,892 mm	
Overall Length	3,260 mm	
Overall Width (min)	1,890 mm	
Height		
Over Exhaust	2,200 mm	
Over Steering Wheel	1,490 mm	
The contract of the contract o		