



Reversible Hydraulic Mould Board Plow

Specifications:-

General	
Application	For Cutting And Inversion Of Soil
Tractor Power	≥ 60 HP
No. of Bottoms	03 Reversible
Reversing Mechanism	Hydraulic And Manually Operated Lever With Locking System
Overall Dimensions (min.)	
Length	3100 mm ± 30 mm

Width	1700 mm \pm 10 mm
Height	1450 mm \pm 10 mm
Material Specifications	
Main Frame	M.S. Pipe 120 mm Dia. 12 mm Wall Thickness And M.S. Shaft 50 mm Dia. With The Support Of M.S. Angle 75 x 75 x 9 mm And Rectangular Bar 80 x 30 mm
Mast (A-Frame)	M.S. Sheet 490 x 12 mm
Crossbar	M.S. Flat 60 x 30 mm
Mould Board	740 x 385 x 6 mm M.S. Sheet
M.B. Extension	M.S. Sheet 100 x 9 mm
Shear	500 x 230 x 11 mm Hardened Steel HRC > 40
Bracket Support	04 Nos. M.S. Plate 640 x 100 x 12 mm 02 Nos. M.S. Plate 345 x 100 x 12 mm
Hydraulic Jack	01 No. 535 mm Long, 22 mm Dia.
Bearings	02 Nos. 32210 And 32215
Miscellaneous	
Paint	Double Coat With Primer After The Surface Finish

Nuts And Bolts	To Be Tightened With Spring Washers
Bearings	European Standard
Warranty	Free: 1 Year For Parts And Service Extended: 5 Years For Parts Supply On Payment

