



**Chisel Plow**  
**(5 Tines)**

**Specifications:-**

General	
Application	For Deep Plowing
No. Of Tines	05 Nos., 2 At The Front, 3 At Rear
Tine Spacing	455 mm, Adjustable
Tractor Power	$\geq 50$ HP
Overall Dimensions	
Length	900 mm $\pm$ 10 mm
Width	1800 mm $\pm$ 20 mm

Height	1100 mm $\pm$ 10 mm
Weight (min.)	325 Kg $\pm$ 5 Kg
<b>Material Specifications</b>	
Main Frame	100 $\times$ 100 $\times$ 6 mm, M.S. Box, 02 Gangs With Side Support Of 100 $\times$ 50 $\times$ 6 mm M.S. Box
Mast (A-Frame)	9 mm M.S. Formed Sheet Formed, Reinforced With 16 mm M.S. Plate
Hitch Frame	62 $\times$ 18 mm, M.S. Plate
Tine Bracket	160 $\times$ 160 $\times$ 15 mm, M.S. Plate, And M.S. Angle 75 $\times$ 9 mm
Tine	100 $\times$ 30 mm, M.S. Plate, 75 $\times$ 9 mm M.S. Angle, And 12 mm Thick M.S. Plate
Shovel	275 $\times$ 60 $\times$ 20 mm Hardened Steel (HRC $\geq$ 30)
<b>Miscellaneous</b>	
Paint	Double Coat With Primer After Surface Finish
Nuts And Bolts	To Be Tightened With Spring Washers
Warranty	Free: 1 Year For Parts And Service Extended: 5 Years For Parts Supply On Payment