



## **Multi Crop Drill**

### **Specifications:-**

<b>General</b>	
Application	For Direct Sowing Of Rice And Other Crops Like Soybean, Peas, Legumes, Beans, Etc.
Type	Tractor Mounted, Trailed Type
Adjustments	Adjustment Of Seed To Major Tillage Practices i.e., Conventional Till, Mulch Or Minimum Till, No-Till
Power Requirement	60 HP – Tractor or Above
No. Of Rows	12 Nos.

Furrow Opener Type	Double Coulter-Disc, Offset
Working Width (min.)	2130 mm (Adjustable)
Seed Hopper Capacity	420 Kg or Above
Fertilizer Hopper Capacity	400 Kg or Above
Row Spacing	177.8 mm
Seed/Fertilizer Hose Type	Rubber Convuluted
Coulter Size (Dia.)	355.6 mm, 4 mm Thick
Disc Size (Dia.)	355.6 mm, 2.5 mm Thick
Coulter Lead Distance	38 mm Apart In Front Of Dual Disc
Soil Disc Penetration Range	Up To 76 mm
Press Wheels (Dia.)	393.7 mm, 50.8 mm Thick
Disc Bearings	Heavy Duty-Sealed Double Row Ball Bearing
Origin	USA, Romania, Italy, U.K, Japan, Germany
Warranty	Free: 1 Year For Parts And Service