



## **Laser Land Leveler**

### **Specifications:-**

<b>TRANSMITTER (MEI – USA; Model: M1000A)</b>	
Heat Resistant (Up To 60 C) And Water Proof	
Tripod Mounting System	
Working Area	Diameter: 1000 m/1 Km (Approx.)
Provision Of Slope	1 mm To 10 Ft.
Accuracy	(+,-) 1.5 mm
Self-Leveling Range	Horizontal (+,-) 5
Rotating Speed	600 – 1200 RPM

Operating Time	With A Battery Of 65 Hrs.  With Dry Cells 25 Hrs.
<b>CONTROL BOX ( MEI – USA; Model: MEI 312)</b>	
Heat & Water Resistant	
Fully Automatic Blade Control For Precision Grading	
Manual or Automatic Control	
On Grade Accuracy Selection	
Operating Temperature	-15 °C to 60 °C
Operating Voltage	12V DC
Weight	1.5 Kg
<b>RECEIVER (MEI – USA; Model: 367 SB)</b>	
Extremely Durable: Internally Protected From Shock & Vibration	
Beam Detecting Angle	360
Height	7.8 (200 mm)
Water Resistant & Dust Proof	
Super Bright LED Display	
Two Intensities	(1) Super Bright For High Ambient Light Levels  (2) Softer For Low Light

Power Source	12 / 24 V DC
<b>LASER SCRAPER</b>	
<b>Dimensions</b>	
Overall Length	4,400 mm (14.4 Ft.)
Overall Width	2,570 mm (8.4 Ft.)
Overall Height	2,000 mm (6.5 Ft.)
Approx. Weight	1,000 Kg
Tires	04 Nos.
Size	6.50 – 14 (6 PR)
<b>HYDRAULIC KIT</b>	
(Aron – Made In Italy)	
<b>COMPATIBLE TRACTORS</b>	
MF 375 (75 HP) And MF 385 (85 HP)	